



C.G.A. Ricambi Srl

Via Canale 13

41013 Castelfranco Emilia (MO)

Tel. 059.920379 – 923429 Fax 059.950071



MARTELLI DEMOLITORI

LS HAMMER

BREAKERS

CARATTERISTICHE TECNICHE - TECHNICAL FEATURES

TIPO MARTELLO	7 C	10 C	10 PS	12 PS	15 S	16 PS	25 JCB	25	25 S	40 PS	55	100	1000 PS	130	1500 PS	2000 PS	3000 PS
	0,8-2,0	1,2-2,5	1,2-2,5	2,0-4,0	3,0-5,0	4,0-6,0	6,0-12	6,0-12	6,0-12	6,0-14	8,0-15	14-22	14-22	17-28	14-22	18-25	25-35
	70	90	110	140	190	230	280	280	280	350	570	1000	835	1300	1300	1620	2500
DIAMETRO UTENSILE	40	45	45	48	64	56	80	80	80	80	95	114	105	120	120	135	150
PORTATA OLIOL/Min	12-30	12-30	12-30	15-25	40-50	30-60	60-100	60-100	60-100	50-80	70-110	110-130	100-130	120-160	90-120	125-150	150-190
PRESSIONE DEMOLITORE Bar	105-115	105-115	105-115	105-115	90	105-125	80	80	110-120	110-120	90	110	160-180	120	120-150	160-180	160-180
PRESSIONE ESCAVATORE Bar	145	145	145	145	100	160	120	120	145	145	130	130	200	200	200	210	210
CONTRO PRESSIONE Bar	1-12	1-12	1-12	1-10	4-5	12	4-5	4-5	12	12	4-5	4-5	15	4-5	15	15	15
ENERGIA D'URTO MAX joule	160	180	180	210	350	450	700	700	720	720	1050	1700	2320	2050	3948	6190	8512
POTENZA INGRESSO MAX Kw	5,5	5,5	5,5	7	5	8	8	8	9	9	9	12,7	26	17	39	51,5	67,4
NR COLPI MINUTO	950-1450	950-1350	950-1350	800-1200	700-1100	540-1540	450-900	450-900	500-950	500-950	380-650	400-500	450-900	350-680	400-750	300-700	300-650
TEMPERATURA OLIO MAX C°	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80
VISCOSITA OLIO Cst	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90	15-90
ATTACCO TUBI INGRESSO	½ G	½ G	½ G	½ G	¾ G	½ G	1 G	¾ G	¾ G	¾ G	1 G	1 G	1 G	1,1/4 G	¾ G	1 G	1 G
ATTACCO TUBI USCITA	½ G	½ G	½ G	¾ G	¾ G	¾ G	1 G	¾ G	¾ G	¾ G	1,1/4 G	1,1/4 G	1,1/4 G	1,1/4 G	¾ G	1 G	1 G
TUBO MANDATA DIAMETRO MIN mm	10	10	10	10	14	14	19	19	14	14	19	19	19	32	19	25	25
TUBO RITORNO DIAMETRO MIN mm	12	12	12	12	21	21	25	25	21	21	25	32	32	32	25	32	32

P=PRESSURIZZATO – PRESSURIZE S=SILENZIATO – SILENCER

