

**DECESPUGLIATRICE IDRAULICA**

## LS7 REV

**HYDRAULIC HEDGE TRIMMER**




### LISTINO PREZZI – PRICELIST

Modello - Model				Cilindrata Displacement	Bar min/max	Oil L/min						
LS7 1300 REV	10/12,0–25,0	1300	650-950	40-50-63	200-350	100-125-160	1x50mm	160-80-85				
LS7 1600 REV	12/15,0–25,0	1600	750-1050	40-50-63	200-350	100-125-160	1x50mm	190-80-85				
	KF 7		HF 6		HF 11 HF 13		HF 14					
LS7 1300 REV	C	40+20	€ 19.281	M	20	€ 19.385,90	F	24	€ 22.370,17	DF	36	€ 23.914,80
LS7 1600 REV	C	40+20	€ 22.370	M	20	€ 22.475,17	F	32	€ 25.392,28	DF	42	€ 26.802,59

### ACCESSORI – ACCESSORIES

Apertura idraulica cofano 1



€ 450,45

Hood 1 hydraulic opening

Apertura meccanica cofano 2



€ 90,09

Hood 2 mechanical opening

### UTENSILI – TOOLS

KF7				HF6				HF11				HF13				HF14				
	KIT	€			KIT	€			KIT	€			KIT	€			KIT	€		
1	147121	1	€ 31,67		1	€ 31,67		1	€ 31,67		4	€ 94,87	1	€ 11,19		1	€ 11,19			
2	UNI 7474-03	1	€ 7,64		2	€ 7,64		1	€ 7,64	3	€ 55,42	3	€ 55,42	2	€ 71,25		1	€ 71,25		
3	141241	2	€ 7,37		3	€ 6,01		2	€ 6,01	4	€ 110,57	4	€ 110,57							
4	TE024	2	€ 8,19		4	€ 28,94		1	€ 28,94											
5	TE029	1	€ 7,92																	
<b>HF11 KIT € 1.820,36</b>				<b>HF14 KIT € 82,45</b>																
<b>HF13 KIT € 2.215,67</b>																				
1	TE060	4	€ 94,87																	
3	TE056	26	€ 55,42																	
1	TE061	4	€ 110,57																	
3	TE056	32	€ 55,42																	








## DECESPUGLIATRICE IDRAULICA

## LS7 REV

## HYDRAULIC HEDGE TRIMMER



Modello - Model				Cilindrata Displacement	Bar min/max	Oil L/min		
LS7 1300 REV	10/12,0-25,0	1300	650-950	40-50-63	200-350	100-125-160	1x50mm	160-80-85
LS7 1600 REV	12/15,0-25,0	1600	750-1050	40-50-63	200-350	100-125-160	1x50mm	190-80-85

### CARATTERISTICHE TECNICHE E DOTAZIONI STANDARD

- Trasmissione moncinghia dentata preallungata HTD ad alte prestazioni.
- Cofanatura interna a doppia cassa con intercapedine.
- Protezione carter cinghie.
- Trinciatrice simmetrica per un taglio più veloce con la rotazione dell'escavatore.
- Bocche d'ingresso e d'uscita completamente identiche.
- Cofani regolabili 01 idraulicamente - 01 meccanico, apribili completamente per una maggiore capacità di taglio.
- Supporti rotore interni con labirinto per la protezione dei cuscinetti dalle impurità.
- Cuscinetti orientabili di prima qualità.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anticavitazione.
- Motore a pistoni.
- Protezioni antinfortunistiche con catene a norma CE.

### TECHNICAL FEATURES AND STANDARD EQUIPMENT

- Toothed high-performance belts transmission.
- Internally reinforced with inside double-case body with interspace.
- Protective belts-cover.
- Shearing symmetric head, for a faster working by the excavator rotation.
- Input and output mouths completely identical, adjustable
- Hydraulic hoods 01 - 01 mechanical, fully openable for higher cutting capacity.
- Inside Rotor Supports with "labyrinth" for the protection of the bearings by the impurities.
- Adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Piston motor.
- Accident prevention chains protections according to EC directives.

### Rotore elicoidale



Helicoidal Rotor

### Rotore forestale mazze a scomparsa



Forestal rotor wood flanged

### Rotore forestale a denti fissi



Forestal rotor fixed teeth

### ACCESSORI

- Apertura idraulica cofano 1
- Apertura meccanica cofano 2

### ACCESSORIES

- Hood 1 hydraulic opening
- Hood 2 mechanical opening

