

DECESPUGLIATRICE IDRAULICA

LS FS10

HYDRAULIC HEDGE TRIMMER



LISTINO PREZZI – PRICELIST

Modello - Model	HP			Cilindrata Displacement	Bar min/max	Oil L/min			
LS FS10 1600	70-120	1300	1150	45-60-80	200-350	100-130-180	1x55mm	170-100-160	
LS FS10 1800	70-120	1800	1420	45-60-80	200-350	100-130-180	1x55mm	220-100-160	
	HF 14								
LS FS10 1600	DF	36	€ 27.669						
LS FS10 1800	DF	48	€ 29.952						

ACCESSORI – ACCESSORIES

<p>Kit elettrovalvola per azionamento cofano frontale</p> <p>€ 601</p> <p>Diverter valve, to active frontal hood</p>		<p>Motore pistoni portata variabile</p> <p>Sovrapprezzo € 3.003 Ricambio € 3.604</p> <p>Extra charge € 3.003 Spare part € 3.604</p> <p>Piston motor, variable displacement</p>
--	--	--

UTENSILI – TOOLS


HF14	KIT	€ 82,45	
1	TE050	€ 11,19	
2	TE046	€ 71,25	







DECESPUGLIATRICE IDRAULICA

LS FS10

HYDRAULIC HEDGE TRIMMER



Modello - Model	HP			Cilindrata Displacement	Bar min/max	Oil L/min		
LS FS10 1600	70-120	1300	1150	45-60-80	200-350	100-130-180	1x55mm	170-100-160
LS FS10 1800	70-120	1800	1420	45-60-80	200-350	100-130-180	1x55mm	220-100-160

CARATTERISTICHE TECNICHE E DOTAZIONI STANDARD

- Attacco fisso universale.
- Arco di protezione.
- Rotore forestale a denti fissi.
- Trasmissione monocinghia dentata preallungata HTD ad alte prestazioni.
- Cofanatura interna a doppia cassa con intercapedine.
- Protezione carter cinghie.
- Cofano frontale idraulico, per una maggiore capacità di taglio.
- Supporti rotore interni con labirinto per la protezione dei cuscinetti dalle impurità.
- Cuscinetti rotore orientabili di prima qualità.
- Manometro per controllo pressione di lavoro.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata olio, antiurto (valvola di max pressione), anti-cavitazione.
- Motore a pistoni.
- Protezioni antinfortunistiche con catene a norma CE.

TECHNICAL FEATURES AND STANDARD EQUIPMENT

- Fixed universal hitch.
- Protective arch.
- Forestal rotor fixed teeth.
- Toothed high-performance belts transmission.
- Internally reinforced with inside double - case body with interspace.
- Protective belts-cover.
- Hydraulic hoods , fully openable for higher cutting capacity.
- Inside Rotor Supports with "labyrinth" for the protection of the bearings by the impurities.
- Adjustable bearings of 1st quality.
- Manometer for working pressure control.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Piston motor.
- Accident prevention chains protections according to EC

Rotore forestale a denti fissi



Forestal rotor fised teeth

ACCESSORI

- Kit elettrovalvola per azionamento cofano frontale.
- Motore a pistoni a portata variabile.

ACCESSORIES

- Diverter valve, to active frontal hood.
- Piston motor, variable displacement.

