



C.G.A. Ricambi Srl

Via Rossini 8
4130 Bastiglia (MO)
Tel. 059.920379 – 923429 Fax 059.950071



DECESPUGLIATRICE IDRAULICA

LS7 REV

HYDRAULIC HEDGE TRIMMER




LISTINO PREZZI – PRICELIST

Modello - Model				Cilindrata Displacement	Bar min/max	Oil L/min						
LS7 1300 REV	10/12,0-25,0	1300	650-950	PV 32-64	200-350	70-160	1x50mm	160-80-85				
LS7 1600 REV	12/15,0-25,0	1600	750-1050	PV 32-64	200-350	70-160	1x50mm	190-80-85				
	KF 7		HF 6		HF 11 HF 13		HF 14					
LS7 1300 REV	C	40+20	€ 19.281	M	20	€ 19.385,90	F	24	€ 22.370,17	DF	36	€ 23.914,80
LS7 1600 REV	C	40+20	€ 22.370	M	20	€ 22.475,17	F	32	€ 25.392,28	DF	42	€ 26.802,59

ACCESSORI – ACCESSORIES

Apertura idraulica cofano 1



€ 450,45

Hood 1 hydraulic opening

Apertura meccanica cofano 2



€ 90,09

Hood 2 mechanical opening

UTENSILI – TOOLS

KF7				KIT	€ 78,35		HF6				KIT	€ 80,26	
1	147121	1	€ 31,67	1	€ 31,67		1	147121	1	€ 31,67	1	€ 31,67	
2	UNI 7474-03	1	€ 7,64	1	€ 7,64		2	UNI 7474-03	1	€ 7,64	1	€ 7,64	
3	141241	2	€ 7,37	2	€ 7,37		3	141244	2	€ 6,01	2	€ 6,01	
4	TE024	2	€ 8,19	2	€ 8,19		4	TE020	1	€ 28,94	1	€ 28,94	
5	TE029	1	€ 7,92	1	€ 7,92								
HF11				KIT	€ 1.820,36		HF14				KIT	€ 82,45	
1	TE060	4	€ 94,87	4	€ 94,87		1	TE050	1	€ 11,19	1	€ 11,19	
3	TE056	26	€ 55,42	26	€ 55,42		2	TE046	1	€ 71,25	1	€ 71,25	
HF13				KIT	€ 2.215,67								
1	TE061	4	€ 110,57	4	€ 110,57								
3	TE056	32	€ 55,42	32	€ 55,42								



DECESPUGLIATRICE IDRAULICA

LS7 REV

HYDRAULIC HEDGE TRIMMER



KF7
Max ø 6 cm








HF6
Max ø 8 cm



HF11-HF13
Max ø 25 cm



HF14
Max ø 25 cm

Modello - Model				Cilindrata Displacement	Bar min/max	Oil L/min		
LS7 1300 REV	10/12,0-25,0	1300	650-950	PV 32-64	200-350	70-160	1x50mm	160-80-85
LS7 1600 REV	12/15,0-25,0	1600	750-1050	PV 32-64	200-350	70-160	1x50mm	190-80-85

CARATTERISTICHE TECNICHE E DOTAZIONI STANDARD

- Trasmissione monocinghia dentata preallungata HTD ad alte prestazioni.
- Cofanatura interna a doppia cassa con intercapedine.
- Protezione carter cinghie.
- Trinciatrice simmetrica per un taglio più veloce con la rotazione dell'escavatore.
- Bocche d'ingresso e d'uscita completamente identiche.
- Cofani regolabili 01 idraulicamente - 01 meccanico, apribili completamente per una maggiore capacità di taglio.
- Supporti rotore interni con labirinto per la protezione dei cuscinetti dalle impurità.
- Cuscinetti orientabili di prima qualità.
- Blocco valvole comprensivo di valvola prioritaria per regolazione della portata AA34 antiurto (valvola di max pressione), anticavitazione.
- Motore a pistoni portata variabile.
- Protezioni antinfortunistiche con catene a norma CE.

TECHNICAL FEATURES AND STANDARD EQUIPMENT

- Toothed high-performance belts transmission.
- Internally reinforced with inside double-case body with interspace.
- Protective belts-cover.
- Shearing symmetric head, for a faster working by the excavator rotation.
- Input and output mouths completely identical, adjustable
- Hydraulic hoods 01 - 01 mechanical, fully openable for higher cutting capacity.
- Inside Rotor Supports with "labyrinth" for the protection of the bearings by the impurities.
- Adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Piston motor.
- Accident prevention chains protections according to EC directives.

Rotore elicoidale



Helicoidal Rotor

Rotore forestale mazze a scomparsa



Forestal rotor wood flanged

Rotore forestale a denti fissi



Forestal rotor fixed teeth

ACCESSORI

- Apertura idraulica cofano 1
- Apertura meccanica cofano 2

ACCESSORIES

- Hood 1 hydraulic opening
- Hood 2 mechanical opening

